
AUTOMATIC PRECISION

## EST-GGP-A-PR Electrical plug for GGP-A-PR






**REMARK**


- Electric plug suitable for gripper side

| DESIGNATION | ITEM NO. | A | B | X |
|---|---|---|---|---|
| **EST-GGP-18-A-PR** | 1-10-45-99-00-EST | 2x M8 | 15-p | GGP-18-A-PR |

ROUND AUTOMATIC

## SWK (SWS) gripper changing system head robot side









**ADVANTAGES**

- V1 - Self-retaining locking system
- V2 - Functional parts made of hardened steel
- V3 - Integrated air feed-through
- V4 - ISO flange pattern

**REMARK**

- Operating principle: piston actuated balls
- Operating pressure range: from 4.5 bar to 6 bar
- Maintenance: permanently lubricated, relubrication after
- 2 million cycles
- Ambient temperature: from 5°C to 60°C
- Material: Functional parts made of hardened steel
- OTHER SIZES AND ACCESSORIES
- ON REQUEST !

**OPTION**

- Adaptation (drilling pattern) to robot or linear robot
- Interrogation for interlocking
- Please order SWO electrical plug separately, not
- included in the scope of delivery

| DESIGNATION | ITEM NO. | A | B | M | N | WEIGHT | X |
|---|---|---|---|---|---|---|---|
| **SWK-011-000-000** | 1-11-10-06-00-SWK | 50 | 16 | 6xM5 | 16Kg | 0.13Kg | SWA-011 |
| **SWK-021-000-000** | 1-11-10-11-00-SWK | 95 | 22,1 | 8xG1/8" | 25Kg | 0.13Kg | SWA-021 |
| **SWK-060-000-000** | 1-11-10-20-00-SWK | 130 | 24 | 8xG1/8" | 75Kg | 1.3Kg | SWA-060 |

**Legend:** M = Number and thread diameter of air connection N = maximum payload Holding force 10N = 1kg X = suitable for automatic gripper base plate SWA.....