
ROUND AUTOMATIC

SWA (SWS) Quick Change System Piston Stroke Control







ADVANTAGES

- V1 - Self-retaining locking system
- V2 - Functional parts made of hardened steel
- V3 - Integrated air feed-through
- V4 - ISO flange pattern

REMARK

- Operating principle: balls actuated via pistons
- Operating pressure range: from 4.5 bar to 6 bar
- Maintenance: permanently lubricated, relubrication after
- 2 million cycles
- Ambient temperature: from 5°C to 60°C
- Material: functional parts made of hardened steel
- OTHER SIZES AND ACCESSORIES ON REQUEST !

OPTION

- - SWO electrical connectors available on request


DESIGNATION	ITEM NO.	A	B	M	N	WEIGHT	X
SWA-011-000-000	1-11-12-06-00-SWA	50	21	6xM5	16Kg	0.09Kg	SWK-011
SWA-021-000-000	1-11-12-10-00-SWA	95	24	8xG1/8"	25Kg	0.3Kg	SWK-021
SWA-040-000-000	1-11-12-14-00-SWA	115	27	8xG1/8	50kg	0.6Kg	SWK-040
SWA-060-000-000	1-11-12-20-00-SWA	130	23	8xG1/8	75kg	0.7Kg	SWK-060
SWA-076-000-000	1-11-12-24-00-SWA	160	31	5xG3/8"	100kg	1.4Kg	SWK-076

Legend: M = Number and thread diameter of air connection N = maximum payload Holding force 10N = 1kg X = suitable for automatic gripper changing system SWK.....

ROUND AUTOMATIC

ADA-SWK-BAR Adapter for SWK with hole pattern adaptation to robot







ADVANTAGES

- V1 - Adapter with customised hole pattern adaptation to your robot system
- V2 - Connection for direct mounting of the Schunk SWK gripper changing system head robot side to your robot flange

REMARK

- Complex version with fitting holes and holes for
- precise adaptation to robots after provision of your
- robot flange data

DESIGNATION	ITEM NO.	X
ADA-SWK-011-BAR	1-11-14-56-00-ADA	SWK-011
ADA-SWK-040-BAR	1-11-14-66-00-ADA	SWK-040
ADA-SWK-060-BAR	1-11-14-70-00-ADA	SWK-060

Legend: X = suitable for Schunk SWK gripper changing system head robot side SWK-.....