
SPP - P13 / PROFILE

SPP-18-18-N Small Prism Profile







ADVANTAGES

- V1 – 3 prisms available
- V2 – 1x form-fit fastening groove
- V3 – 2 front holes for M4 thread
- V4 – Pipe cross-section
- V5 – new design

REMARK

- All custom lengths are cut to size as required
- Silver anodised finish
- Custom lengths available on request; maximum length 6000mm
- Note:
- - Cheaper by 2m for EU delivery

ORDERING SPECIAL LENGTHS VIA THE CUSTOMER PORTAL

- - please add up the required lengths and order as one item
- 1-15-80-00-43-SPP
- as a single position
- - order the quantity of sawn-to-size cuts 9-95-90-91-00-ZUS
- accordingly as well
- - enter the
- quantities and individual lengths in the comment field of the order overview
- Example order for:
- two profiles SPP-18-18-P13-N in the lengths
- 1× 519mm and 1× 410mm (text for comment field).
- The positions to be ordered are:
- 929 pieces 1-15-80-00-43-SPP
- 2 pieces 9-95-90-91-00-ZUS

STATIC VALUES

- A = 1.412 cm²
- Ex = 0.90 cm
- Ey = 0.90 cm
- Ix = 0.36 cm⁴
- Iy = 0.47 cm⁴
- Wx = 0.34 cm³
- Wy = 0.53 cm³
- Weight = 0.383 kg/m
- Tensile strength 205 N/mm²

DESIGNATION	ITEM NO.	C	D	WEIGHT
SPP-18-18-P13-N-0001	1-15-80-00-43-SPP	1	M4	0.367Kg
SPP-18-18-P13-N-500	1-15-80-00-45-SPP	500	M4	0.185Kg
SPP-18-18-P13-N-1000	1-15-80-00-50-SPP	1000	M4	0.367Kg
SPP-18-18-P13-N-1500	1-15-80-00-55-SPP	1500	M4	0.555Kg
SPP-18-18-P13-N-2000	1-15-80-00-60-SPP	2000	M4	0.734Kg
SPP-18-18-P13-N-6000	1-15-80-00-69-SPP	6000	M4	2.202Kg

Legend: C = Dimensions in mm D = for thread .....