

SPP - P13 / PROFILE

SPP-36-18 PreciGrip Profile







ADVANTAGES

- V1 – 6 prisms available
- V2 – 6 front mounting holes for M4 thread

REMARK

- All custom lengths are cut to size as required
- Silver anodised finish
- Note:
- - Cheaper by 2m for EU delivery

ORDERING SPECIAL LENGTHS VIA THE CUSTOMER PORTAL

- - please add the required lengths and order with item
- 1-15-81-50-01-SPP
- as a single item
- - to order the required number of saw cuts 9-95-90-91-00-ZUS
- - enter the quantities and individual lengths
- in the comments field of the order summary
- Example order for:
- two SPP-36-18 profiles in the lengths
- 1× 519mm and 1× 410mm (text for comment field).
- The items to be ordered are:
- 929 pieces 1-15-81-50-01-SPP
- 2 pieces 9-95-90-91-00-ZUS

STATIC VALUES

- A = 2.568 cm²
- Ex = 0.9 cm
- Ey = 1.8 cm
- Ix = 0.92 cm⁴
- Iy = 3.34 cm⁴
- Wx = 1.02 cm³
- Wy = 1.85 cm³
- Weight = 0.696 kg/m
- Tensile strength 205 N/mm²

DESIGNATION	ITEM NO.	C	D	WEIGHT
SPP-36-18-P13-500	1-15-80-01-20-SPP	500	M4	0.348Kg
SPP-36-18-P13-1000	1-15-80-01-30-SPP	1000	M4	0.696Kg
SPP-36-18-P13-1500	1-15-80-01-40-SPP	1500	M4	1.044Kg
SPP-36-18-P13-2000	1-15-80-01-50-SPP	2000	M4	1.392Kg
SPP-36-18-P13-50	1-15-81-30-05-SPP	50	M4	0.035Kg
SPP-36-18-P13-100	1-15-81-30-10-SPP	100	M4	0.07Kg
SPP-36-18-P13-150	1-15-81-30-15-SPP	150	M4	0.104Kg
SPP-36-18-P13-200	1-15-81-30-20-SPP	200	M4	0.139Kg
SPP-36-18-P13-250	1-15-81-30-25-SPP	250	M4	0.174Kg
SPP-36-18-P13-300	1-15-81-30-30-SPP	300	M4	0.209Kg
SPP-36-18-P13-350	1-15-81-30-35-SPP	350	M4	0.244Kg
SPP-36-18-P13-400	1-15-81-30-40-SPP	400	M4	0.278Kg
SPP-36-18-P13-450	1-15-81-30-45-SPP	450	M4	0.313Kg
SPP-36-18-P13-550	1-15-81-30-55-SPP	550	M4	0.383Kg
SPP-36-18-P13-600	1-15-81-30-60-SPP	600	M4	0.418Kg
SPP-36-18-P13-650	1-15-81-30-65-SPP	650	M4	0.452Kg
SPP-36-18-P13-700	1-15-81-30-70-SPP	700	M4	0.487Kg
SPP-36-18-P13-750	1-15-81-30-75-SPP	750	M4	0.522Kg