
MPP - P22 / PROFILE

MPP-30-15 Middle Prism Profile







ADVANTAGES

- V1 – 2 prisms available
- V2 – Tube cross-section

ORDERING SPECIAL LENGTHS VIA THE CUSTOMER PORTAL

- - Please add the required lengths and order with item
- 1-15-80-02-01-MPP
- as a single item
- - Number of saw cuts 9-95-90-91-00-ZUS
- order accordingly
- - In the comments field of the order overview
- enter quantities and individual lengths
- Example order for:
- Two MPP-30-15-P22 profiles in the lengths
- 1× 519mm and 1× 410mm (text for comment field).
- The items ordered are:
- 929 pieces 1-15-80-02-01-MPP
- 2 pieces 9-95-90-91-00-ZUS

STATIC VALUES

- A = 0.153 cm²
- Ex = 1.50 cm
- Ey = 0.75 cm
- Ix = 0.37 cm⁴
- Iy = 1.21 cm⁴
- Wx = 0.50 cm³
- Wy = 0.81 cm³
- Weight = 0.430 kg/m
- Tensile strength 205 N/mm²

DESIGNATION	ITEM NO.	C	WEIGHT
MPP-30-15-P22-0001	1-15-80-02-01-MPP	1	0.413Kg
MPP-30-15-P22-0500	1-15-80-02-05-MPP	500	0.207Kg
MPP-30-15-P22-1000	1-15-80-02-10-MPP	1000	0.413Kg
MPP-30-15-P22-1500	1-15-80-02-15-MPP	1500	0.62Kg
MPP-30-15-P22-2000	1-15-80-02-20-MPP	2000	0.826Kg
MPP-30-15-P22-6000	1-15-80-02-29-MPP	6000	2.478Kg
MPP-30-15-P22-50	1-15-81-08-05-MPP	50	0.022Kg
MPP-30-15-P22-100	1-15-81-08-10-MPP	100	0.043Kg
MPP-30-15-P22-150	1-15-81-08-15-MPP	150	0.065Kg
MPP-30-15-P22-200	1-15-81-08-20-MPP	200	0.086Kg
MPP-30-15-P22-250	1-15-81-08-25-MPP	250	0.108Kg
MPP-30-15-P22-300	1-15-81-08-30-MPP	300	0.129Kg
MPP-30-15-P22-350	1-15-81-08-35-MPP	350	0.151Kg
MPP-30-15-P22-400	1-15-81-08-40-MPP	400	0.172Kg
MPP-30-15-P22-450	1-15-81-08-45-MPP	450	0.194Kg
MPP-30-15-P22-550	1-15-81-08-55-MPP	550	0.237Kg
MPP-30-15-P22-600	1-15-81-08-60-MPP	600	0.258Kg
MPP-30-15-P22-650	1-15-81-08-65-MPP	650	0.28Kg
MPP-30-15-P22-700	1-15-81-08-70-MPP	700	0.301Kg
MPP-30-15-P22-750	1-15-81-08-75-MPP	750	0.323Kg
MPP-30-15-P22-800	1-15-81-08-80-MPP	800	0.344Kg
MPP-30-15-P22-850	1-15-81-08-85-MPP	850	0.366Kg
MPP-30-15-P22-900	1-15-81-08-90-MPP	900	0.387Kg