
DESIGNATION	ITEM NO.	C	WEIGHT
MPP-30-15-P22-950	1-15-81-08-95-MPP	950	0.409Kg

Legend: C = Dimensions in mm

MPP - P22 / PROFILE

MPP-30-30 Middle Prism Profile







ADVANTAGES

- V1 – 4 prisms available
- V2 – 4 front holes for M5 thread
- V3 – Absorption of high torsional forces
- V4 – Pipe cross-section

REMARK

- All custom lengths are cut to size as required
- Silver anodised finish
- Custom lengths available on request; max. length 6000mm
- Note:
- - Cheaper by 2m for EU delivery

ORDERING SPECIAL LENGTHS VIA THE CUSTOMER PORTAL

- - Please add the required lengths and order with item
- 1-15-80-02-23-MPP
- as a single item
- - Number of saw cuts 9-95-90-91-00-ZUS
- order accordingly
- - In the comments field of the order overview
- enter quantities and individual lengths
- Example order for:
- two MPP-30-30-P22 profiles in the lengths
- 1× 519mm and 1× 410mm (text for comment field).
- The items to be ordered:
- 929 pieces 1-15-80-02-23-MPP
- 2 pieces 9-95-90-91-00-ZUS

STATIC VALUES

- A = 3.432 cm²
- Ex = 1.50 cm
- Ey = 1.50 cm
- Ix = 3.2 cm⁴
- Iy = 3.2 cm⁴
- Wx = 2.13 cm³
- Wy = 2.13 cm³
- Weight = 0.93 kg/m
- Tensile strength 205 N/mm²

DESIGNATION	ITEM NO.	C	D	WEIGHT
MPP-30-30-P22-0001	1-15-80-02-23-MPP	1	M5	0.001Kg
MPP-30-30-P22-500	1-15-80-02-25-MPP	500	M5	0.465Kg
MPP-30-30-P22-1000	1-15-80-02-30-MPP	1000	M5	0.93Kg
MPP-30-30-P22-1500	1-15-80-02-35-MPP	1500	M5	1.395Kg
MPP-30-30-P22-2000	1-15-80-02-40-MPP	2000	M5	1.86Kg
MPP-30-30-P22-6000	1-15-80-02-49-MPP	6000	M5	5.58Kg
MPP-30-30-P22-50	1-15-81-11-05-MPP	50	M5	0.047Kg
MPP-30-30-P22-100	1-15-81-11-10-MPP	100	M5	0.093Kg
MPP-30-30-P22-150	1-15-81-11-15-MPP	150	M5	0.14Kg
MPP-30-30-P22-200	1-15-81-11-20-MPP	200	M5	0.186Kg
MPP-30-30-P22-250	1-15-81-11-25-MPP	250	M5	0.233Kg