
DESIGNATION	ITEM NO.	C	D	WEIGHT
MPP-30-30-P22-300	1-15-81-11-30-MPP	300	M5	0.279Kg
MPP-30-30-P22-350	1-15-81-11-35-MPP	350	M5	0.326Kg
MPP-30-30-P22-400	1-15-81-11-40-MPP	400	M5	0.372Kg
MPP-30-30-P22-450	1-15-81-11-45-MPP	450	M5	0.419Kg
MPP-30-30-P22-550	1-15-81-11-55-MPP	550	M5	0.51Kg
MPP-30-30-P22-600	1-15-81-11-60-MPP	600	M5	0.558Kg
MPP-30-30-P22-650	1-15-81-11-65-MPP	650	M5	0.605Kg
MPP-30-30-P22-700	1-15-81-11-70-MPP	700	M5	0.651Kg
MPP-30-30-P22-750	1-15-81-11-75-MPP	750	M5	0.698Kg
MPP-30-30-P22-800	1-15-81-11-80-MPP	800	M5	0.74Kg
MPP-30-30-P22-850	1-15-81-11-85-MPP	850	M5	0.791Kg
MPP-30-30-P22-900	1-15-81-11-90-MPP	900	M5	0.837Kg
MPP-30-30-P22-950	1-15-81-11-95-MPP	950	M5	0.884Kg

Legend: C = Dimensions in mm D = for threads .....

MPP - P22 / PROFILE

MPP-30-30-N Middle Prism Profile







ADVANTAGES

- V1 – 3 prisms provided for direct mounting
- V2 – 1x form-fitting mounting groove
- V3 – Pipe cross-section

ORDERING SPECIAL LENGTHS VIA THE CUSTOMER PORTAL

- - Please add the desired lengths and order with item
- 1-15-80-02-43-MPP
- as a single item
- - Number of saw cuts 9-95-90-91-00-ZUS
- order accordingly
- - Enter the quantities and individual lengths in the comments field of the order overview
- Example order for:
- two MPP-30-30-P22-N profiles in the lengths
- 1× 519mm and 1× 410mm (text for comment field).
- The following items have been ordered:
- 929 pieces 1-15-80-02-43-MPP
- 2 pieces 9-95-90-91-00-ZUS

STATIC VALUES

- A = 2.91 cm²
- Ex = 1.50 cm
- Ey = 1.50 cm
- Ix = 2.72 cm⁴
- Iy = 2.85 cm⁴
- Wx = 1.81 cm³
- Volume = 1.90 cm³
- Weight = 0.788 kg/m
- Tensile strength 205 N/mm²

DESIGNATION	ITEM NO.	C	WEIGHT
MPP-30-30-P22-N-0001	1-15-80-02-43-MPP	1	0.001Kg
MPP-30-30-P22-N-0500	1-15-80-02-45-MPP	500	0.392Kg
MPP-30-30-P22-N-1000	1-15-80-02-50-MPP	1000	0.783Kg
MPP-30-30-P22-N-1500	1-15-80-02-55-MPP	1500	1.175Kg
MPP-30-30-P22-N-2000	1-15-80-02-60-MPP	2000	1.488Kg