
DESIGNATION	ITEM NO.	C	D	WEIGHT
MPP-60-30-P22-350	1-15-81-14-35-MPP	350	M5	0.552Kg
MPP-60-30-P22-400	1-15-81-14-40-MPP	400	M5	0.631Kg
MPP-60-30-P22-450	1-15-81-14-45-MPP	450	M5	0.71Kg
MPP-60-30-P22-550	1-15-81-14-55-MPP	550	M5	0.868Kg
MPP-60-30-P22-600	1-15-81-14-60-MPP	600	M5	0.947Kg
MPP-60-30-P22-650	1-15-81-14-65-MPP	650	M5	1.026Kg
MPP-60-30-P22-700	1-15-81-14-70-MPP	700	M5	1.104Kg
MPP-60-30-P22-750	1-15-81-14-75-MPP	750	M5	1.183Kg
MPP-60-30-P22-800	1-15-81-14-80-MPP	800	M5	1.262Kg
MPP-60-30-P22-850	1-15-81-14-85-MPP	850	M5	1.341Kg
MPP-60-30-P22-900	1-15-81-14-90-MPP	900	M5	1.42Kg
MPP-60-30-P22-950	1-15-81-14-95-MPP	950	M5	1.499Kg

Legend: C = Dimensions in mm D = for thread .....

MPP - P22 / PROFILE

MPP-60-60 Middle Prism Profile







ADVANTAGES

- V1 – 8 prisms available
- V2 – 4 front holes for M5 thread
- V3 – Tube cross-section

REMARK

- Alle custom lengths are cut to size as required
- Silver anodised finish
- Custom lengths available on request; max. length 6000mm
- Note:
- - Cheaper by 2m for EU delivery

ORDERING SPECIAL LENGTHS VIA THE CUSTOMER PORTAL

- - Please add the required lengths and order with item
- 1-15-80-04-03-MPP
- as a single item
- - Number of saw cuts 9-95-90-91-00-ZUS
- order accordingly
- - In the comments field of the order overview
- enter quantities and individual lengths
- Example order for:
- Two MPP-60-60-P22 profiles in the lengths
- 1× 519mm and 1× 410mm (text for comment field).
- The items ordered are:
- 929 pieces 1-15-80-04-03-MPP
- 2 pieces 9-95-90-91-00-ZUS

STATIC VALUES

- A = 11.916 cm^2
- Ex = 3.00 cm
- Ey = 3.00 cm
- Ix = 49.02 cm^4
- Iy = 49.02 cm^4
- Wx = 16.34 cm^3
- Wy = 16.34 cm^3
- Weight = 3.216 kg/m
- Tensile strength 205 N/mm^2

DESIGNATION	ITEM NO.	C	D	WEIGHT
MPP-60-60-P22-0001	1-15-80-04-03-MPP	1	M5	0.003Kg