

PPV-P Profile Parallel connection Prism







ADVANTAGES

- V1 - Stable positive and non-positive connection
- of components or profiles with a prism
- with each other
- V2 - Milled from solid material
- V3 - Profiles can be butt-joined
- V4 - no holes need to be drilled


REMARK


- Material: aluminium


DESIGNATION	ITEM NO.	A	B	C	D	X	WEIGHT
PPV-P13-P13-1	1-25-50-30-00-PPV	P13	P13	1	12	SPP	
PPV-P13-P13-2	1-25-50-32-00-PPV	P13	P13	2	20	SPP	0.009Kg
PPV-P13-P22-2	1-25-50-35-00-PPV	P13	P22	1	12	SPP/MPP	0.026Kg
PPV-P13-P22-2	1-25-50-38-00-PPV	P13	P22	2	25	SPP/MPP	0.026Kg
PPV-P22-P22-2	1-25-50-42-00-PPV	P22	P22	2	25	MPP	0.024Kg
PPV-P22-P22-2-40	1-25-50-43-00-PPV	P22	P22	2	40	MPP	0.036Kg
PPV-P13-P13-3-100	1-25-50-46-00-PPV	P13	P13	3	100	SPP	0.031Kg
PPV-P22-P22-4-160	1-25-50-47-00-PPV	P22	P22	4	160	SPP	0.114Kg
PPV-P22-P22-5-250	1-25-50-48-00-PPV	P22	P22	5	250	MPP	0.172Kg
PPV-P22-P22-3-50	1-25-50-49-00-PPV	P22	P22	3	50	MPP	0.048Kg

Legend: C = number of screws X = suitable for profile .....

WIV-P Profile Connection Prism 90° Prism







ADVANTAGES

- V1 - Universal connector
- V2 - Stable 90° connection


REMARK


- Material: Aluminium


DESIGNATION	ITEM NO.	A	B	C	D	WEIGHT	X
WIV-1-P13-P13	1-25-50-30-00-WIV	P13	P13	1	1	0.01Kg	SPP
WIV-2-2-P13-P13	1-25-50-32-00-WIV	P13	P13	2	2	0.017Kg	SPP
WIV-3-3-P13-P13	1-25-50-34-00-WIV	P13	P13	3	3		SPP
WIV-2-2-P13-P22	1-25-50-36-00-WIV	P13	P22	2	2	0.048Kg	SPP/MPP
WIV-3-3-P22-P22	1-25-50-39-00-WIV	P22	P22	3	3	0.096Kg	MPP
WIV-2-2-P22-P22	1-25-50-40-00-WIV	P22	P22	2	2	0.043Kg	MPP

Legend: C/D = number of screws per profile X = suitable for profile .....

KVP-A-P-P Clamp Prism Outside







ADVANTAGES

- V1 - very stable and slim clamp connection
- of components and profiles with prisms
- V2 - Milled from solid material
- V3 - Angular accuracy
- V4 - no loss of space due to spacers
- (profile lies on profile)

REMARK

- Material: Aluminium