


SG0 Vacuum Cup Oval (complete)







ADVANTAGES

- V1 - extremely lightweight (aluminium adapter)
- V2 - All adapters with hex socket
- V3 - Quick installation
- V4 - for assembly with a ring spanner or
- hex key

REMARK

- To protect the material, all suction cups are only fitted with the adapter upon request.
- Availability is guaranteed.
- Adapters with internal thread available on request
- Contents:
- ASG adapter and PDR pneumatic sealing ring

INFO

- Material: Silicone (S)
- Colour: white
- Shore hardness: 55 +/- 5
- Temperature range: -30°C to 200°C
- Flexibility: ***
- Abrasion resistance: -
- Resistance to oil: -
- Food contact suitability: ***
- Application: Textured surfaces
- For optimal impression results, please clean the
- suction surfaces with a lint-free cloth
- and acetone !
- Material: High-performance elastomer (HE)
- Colour: blue
- Shore hardness: 60 +/- 5
- Temperature resistance: -20°C to 150°C
- Flexibility: *
- Abrasion resistance: **
- Resistance to oil: **
- Application: Painting plastic parts,
- leaves no marks
- For optimal impression results, please clean the
- suction surfaces with a lint-free cloth
- and acetone!
- Material: Nitrile (NBR)
- Colour: black
- Shore hardness: 60 +/- 5
- Temperature resistance: -0°C to 80°C
- Flexibility: *
- Abrasion resistance: **
- Resistance to oil: **

DESIGNATION	ITEM NO.	A	B	C	D	L	M	N	O	WEIGHT	X
SGO-2-4-HE-5	1-55-10-10-00-SG0	2	4	11	M5	1	1N	ASG-10-5	HE	0.001Kg	-
SGO-3,5-7-HE-5	1-55-10-14-00-SG0	3,5	7	12	M5	1	3N	ASG-10-5	HE	0.001Kg	-
SGO-5-15-HE-5	1-55-10-18-00-SG0	5	15	18	M5	1	4N	ASG-12-5	HE	0.002Kg	-
SGO-6-18-HE-5	1-55-10-22-00-SG0	6	18	18	M5	1	4N	ASG-12-5	HE	0.002Kg	-
SG0-8-24-HE-5	1-55-10-24-00-SG0	8	24	18	M5	1	8N	ASG-13-5	HE	0.002Kg	-
SGO-8-24-HE-18	1-55-10-26-00-SG0	8	24	18	G1/8	1	8N	ASG-14-18	HE	0.005Kg	-
SGO-10-30-HE-18	1-55-10-30-00-SG0	10	30	18	G1/8	1	8N	ASG-14-18	HE	0.005Kg	-
SG0-15-45-HE-18	1-55-10-32-00-SG0	15	45	27	G1/8	2,5	10N	ASG-18-18	HE	0.013Kg	1
SGO-15-45-HE-14	1-55-10-34-00-SG0	15	45	28	G1/4	2,5	10N	ASG-16-14	HE	0.017Kg	1
SG0-20-60-HE-18	1-55-10-36-00-SG0	20	60	28	G1/8	2,5	20N	ASG-18-18	HE	0.016Kg	1
SGO-20-60-HE-14	1-55-10-38-00-SG0	20	60	28	G1/4	2,5	20N	ASG-16-14	HE	0.019Kg	1