

DESIGNATION	ITEM NO.	A	B	C	L	M	N	O	SW	WEIGHT
SG1-60-S-14	1-55-14-70-00-SG1	60	33	G1/4	4	ASG-52-14	123N	S	5	0.03Kg
SG1-60-HE-14	1-55-14-73-00-SG1	60	33	G1/4	4	ASG-52-14	123N	HE	5	0.03Kg
SG1-80-S4	1-55-14-76-00-SG1	80	33	G1/4	6	ASG-52-14	198N	S	5	0.059Kg
SG1-80-HE-14	1-55-14-79-00-SG1	80	33	G1/4	6	ASG-52-14	198N	HE	5	0.059Kg
SG1-95-S-14	1-55-14-82-00-SG1	95	34	G1/4	5	ASG-52-14	180N	S	5	0.096Kg
SG1-95-HE-14	1-55-14-84-00-SG1	95	34	G1/4	5	ASG-52-14	180N	HE	5	0.096Kg
SG1-2-N-5	1-55-15-10-00-SG1	2	14	M5	1	ASG-40-5	0,11N	NBR	---	0.001Kg
SG1-3,5-N-5	1-55-15-13-00-SG1	3,5	14	M5	1	ASG-40-5	0,34N	NBR	---	0.001Kg
SG1-5-N-5	1-55-15-19-00-SG1	5	16	M5	1	ASG-42-5	0,67N	NBR	2	0.001Kg
SG1-8-N-5	1-55-15-25-00-SG1	8	16,5	M5	1	ASG-42-5	1,7N	NBR	2	0.001Kg
SG1-10-N-5	1-55-15-31-00-SG1	10	17	M5	9,5	ASG-42-5	2,8N	NBR	2	0.001Kg
SG1-15-N-5	1-55-15-37-00-SG1	15	18	M5	2	ASG-44-5	6,5N	NBR	2	0.002Kg
SG1-20-N-5	1-55-15-42-00-SG1	20	16	M5	2,5	ASG-45-5	12,2N	NBR	3	0.005Kg
SG1-20-N-18	1-55-15-43-00-SG1	20	16	G1/8	2,5	ASG-46-18	12,2N	NBR	3	0.005Kg
SG1-25-N-5	1-55-15-48-00-SG1	25	27	M5	3	ASG-47-5	16,7N	NBR	4	0.006Kg
SG1-25-N-18	1-55-15-49-00-SG1	25	27	G1/8	3	ASG-48-18	16,7N	NBR	4	0.006Kg
SG1-30-N-18	1-55-15-55-00-SG1	30	25	G1/8	2	ASG-48-18	22,7N	NBR	4	0.007Kg
SG1-40-N-18	1-55-15-61-00-SG1	40	27	G1/8	2	ASG-48-18	48N	NBR	4	0.011Kg
SG1-50-N-18	1-55-15-67-00-SG1	50	28	G1/8	2	ASG-50-18	75N	NBR	5	0.03Kg
SG1-50-N-18 Vacuum Cup 1 Bellow	1-55-15-68-00-SG1	50	28	G1/4	2	ASG-50-18	75N	NBR	5	0.03Kg
SG1-60-N-14	1-55-15-73-00-SG1	60	33	G1/4	5	ASG-52-14	123N	NBR	5	0.03Kg
SG1-80-N-14	1-55-15-79-00-SG1	80	33	G1/4	7	ASG-52-14	198N	NBR	5	0.059Kg
SG1-95-N-14	1-55-15-84-00-SG1	95	34	G1/4	6	ASG-52-14	180N	NBR	5	0.096Kg


Legend: L = Suction pad stroke M = adapter N = Holding force with 2-fold safety and 90% vacuum holding force 10N = 1kg O = Material (see legend)

SG1 / VACUUM CUP 1 EDGE (COMPLETE)

SG1-P Vacuum Cup with 1 Bellow (complete) PU







ADVANTAGES

- V1 - Suction on curved surfaces
- V2 - extremely lightweight (aluminium adapter)
- V3 - All adapters with hexagon socket
- V4 - Quick assembly

REMARK

- To protect the material, all suction pads are only fitted with the adapter on request. Availability is guaranteed.
- Adapter with internal thread on request
- Scope of delivery:
- Adapter ASG and pneumatic sealing ring PDR

INFO

- Material: Polyurethane elastomer PU
- Colour: light brown
- Shore hardness: 65 to 95 Shore A
- Temperature resistance: -40°C to +80°C,
- briefly up to 130°C
- Flexibility: *
- Abrasion resistance: ***
- Resistance to oil: **
- Compatibility with foodstuffs: -
- Area of application: for harsh environmental conditions