


SG1 / VACUUM CUP 1 EDGE (COMPLETE)

SG1-PU-EH-LC Vacuum Cup with 1 Bellow polyurethane compl one hardness







ADVANTAGES

- V1 - these PU suction cups are made with single hardening from a specially developed polyurethane. This material combines the elasticity of rubber with the holding power of plastic
- V2 - The suction pads are available in two different Shore hardnesses (40 and 60°Shore)
- V3 - Key features are good elasticity and flexibility, high tensile strength with high wear resistance
- V4 - Virtually silicone and impression-free

REMARK

- Scope of delivery:
- including adapter and seal

INFO

- Material: PU specially developed polyurethane with single hardness
- Shore hardness:
- blue suction cup: 60 °Shore
- yellow suction cup: 40 °Shore
- Temperature resistance: 10°C to +50°C
- Flexibility: **
- Wear resistance: ***
- Resistance to oil: ***
- Compatibility with food: -

DESIGNATION	ITEM NO.	A	B	C	K	L	M	N	O	WEIGHT
SG1-20-PU-EH-40-18-LC	1-57-72-09-00-SG1	22	15	G1/8	40	2	ASG-202-18	7,5N	PU	0.005Kg
SG1-20-PU-EH-60-18-LC	1-57-72-10-00-SG1	22	15	G1/8	60	2	ASG-202-18	7,5N	PU	0.005Kg
SG1-30-PU-EH-40-18-LC	1-57-72-13-00-SG1	31	20,5	G1/8	40	2	ASG-202-18	16,2N	PU	0.006Kg
SG1-30-PU-EH-60-18-LC	1-57-72-14-00-SG1	31	20,5	G1/8	60	2	ASG-202-18	16,2N	PU	0.006Kg
SG1-40-PU-EH-40-18-LC	1-57-72-15-00-SG1	41	24,5	G1/8	40	2,5	ASG-203-18	28N	PU	0.014Kg
SG1-40-PU-EH-60-18-LC	1-57-72-16-00-SG1	41	24,5	G1/8	60	2,5	ASG-203-18	28N	PU	0.014Kg
SG1-40-PU-EH-40-14-LC	1-57-72-17-00-SG1	41	24,5	G1/4	40	2,5	ASG-204-14	28N	PU	0.014Kg
SG1-40-PU-EH-60-14-LC	1-57-72-18-00-SG1	41	24,5	G1/4	60	2,5	ASG-204-14	28N	PU	0.014Kg
SG1-60-PU-EH-40-38-LC	1-57-72-31-00-SG1	62	14,5	G3/8	60	3	-	66N	PU	0.038Kg
SG1-60-PU-EH-60-38-LC	1-57-72-32-00-SG1	62	14,5	G3/8	60	3	-	66N	PU	0.038Kg
SG1-80-PU-EH-60-38-LC	1-57-72-50-00-SG1	81,5	17,5	G3/8	60	3	-	120N	PU	0.07Kg

Legend: K = Degree of hardness lip and bellows °Shore A L = Suction pad stroke M = adapter N = Holding force (vertical lifting direction) at vacuum -0.6 bar, 2-fold safety, holding force 10N = 1kg O = Material (see legend)