

SG2 / VACUUM CUP 2 EDGE (COMPLETE)

SG2 Vacuum Cup with 2 Bellows (complete)







ADVANTAGES

- V1 - Suction on curved surfaces
- V2 - extremely light (aluminium adapter)
- V3 - All adapters with hexagon socket
- V4 - Quick assembly

REMARK

- To protect the material, all suction pads are only fitted with the adapter on request. Availability is guaranteed.
- Adapter with internal thread on request
- Scope of delivery:
- Adapter ASG and pneumatic sealing ring PDR

INFO

- Material: High-performance elastomer (HE)
- Colour: blue
- Shore hardness: 60 +/- 5
- Temperature resistance: -20°C to 150°C
- Flexibility: *
- Abrasion resistance: **
- Resistance to oil: **
- Compatibility with food: -
- Area of application: Painting of plastic parts, leaves no imprint
- For optimum imprint behaviour, please clean the absorbent surfaces with a lint-free cloth and acetone !
- Material: Nitrile (NBR)
- Colour: black
- Shore hardness: 60 +/- 5
- Temperature resistance: -0°C to 80°C
- Flexibility: *
- Abrasion resistance: *
- Resistance to oil: **
- Compatibility with food: -

DESIGNATION	ITEM NO.	A	B	C	L	M	N	O	WEIGHT	SW
SG2-10-S-5	1-55-18-05-00-SG2	10	23	M5	4,5	ASG-42-5	2,4N	S	0.002Kg	
SG2-10-HE-5	1-55-18-07-00-SG2	10	23	M5	7,5	ASG-42-5	2,4N	HE	0.002Kg	---
SG2-10-HE-18	1-55-18-08-00-SG2	10	23	G1/8	7,5	ASG-70-18	2,4N	HE	0.005Kg	---
SG2-15-S-5	1-55-18-10-00-SG2	15	26	M5	7	ASG-42-5	3,5N	S	0.002Kg	---
SG2-15-S-18	1-55-18-11-00-SG2	15	26	G1/8	7	ASG-70-18	3,5N	S	0.005Kg	---
SG2-15-HE-5	1-55-18-12-00-SG2	15	26	M5	7	ASG-42-5	3,5N	HE	0.002Kg	---
SG2-15-HE-18	1-55-18-13-00-SG2	15	26	G1/8	7	ASG-70-18	3,5N	HE	0.005Kg	---
SG2-20-S-5	1-55-18-33-00-SG2	20	28	M5	8,5	ASG-49-5	7,7N	S	0.006Kg	2
SG2-20-S-18	1-55-18-34-00-SG2	20	28	G1/8	8,5	ASG-48-18	7,7N	S	0.007Kg	3
SG2-20-HE-5	1-55-18-35-00-SG2	20	28	M5	8,5	ASG-49-5	7,7N	HE	0.006Kg	2
SG2-20-HE-18	1-55-18-36-00-SG2	20	28	G1/8	8,5	ASG-48-18	7,7N	HE	0.007Kg	3
SG2-30-S-18	1-55-18-51-00-SG2	30	37,5	G1/8	11,5	ASG-48-18	19,2N	S	0.012Kg	4
SG2-30-S-14	1-55-18-52-00-SG2	30	37,5	G1/4	11,5	ASG-82-14	19,2N	S	0.012Kg	4
SG2-33-HE-18	1-55-18-55-00-SG2	33	34,5	G1/8	11,5	ASG-58-18	19,2N	HE	0.012Kg	4
SG2-33-HE-14	1-55-18-57-00-SG2	33	34,5	G1/4	11,5	ASG-62-14	19,2N	HE	0.015Kg	4
SG2-40-S-18	1-55-18-61-00-SG2	40	45	G1/8	10	ASG-48-18	28N	S	0.02Kg	4
SG2-40-S-14	1-55-18-62-00-SG2	40	37,5	G1/4	10	ASG-82-14	28N	S	0.012Kg	4
SG2-43-HE-18	1-55-18-63-00-SG2	43	35	G1/8	10	ASG-58-18	28N	HE	0.018Kg	5
SG2-43-HE-14	1-55-18-65-00-SG2	43	35	G1/4	10	ASG-62-14	28N	HE	0.021Kg	5
SG2-50-S-18	1-55-18-71-00-SG2	50	50	G1/8	18	ASG-50-18	59N	S	0.028Kg	5
SG2-50-S-14	1-55-18-72-00-SG2	50	50	G1/4	18	ASG-80-14	59N	S	0.028Kg	5