

DESIGNATION	ITEM NO.	A	B	C	L	M	N	O	WEIGHT	SW
SG2-53-HE-18	1-55-18-74-00-SG2	53	41	G1/8	18	ASG-58-18	59N	HE	0.018Kg	5
SG2-53-HE-14	1-55-18-76-00-SG2	53	41	G1/4	18	ASG-62-14	59N	HE	0.021Kg	5
SG2-75-S-14	1-55-18-90-00-SG2	75	57	G1/4	17	ASG-52-14	152N	S	0.089Kg	5
SG2-75-HE-14	1-55-18-93-00-SG2	75	57	G1/4	17	ASG-52-14	152N	HE	0.089Kg	5
SG2-10-N-5	1-55-19-07-00-SG2	10	23	M5	4,5	ASG-42-5	2,4N	NBR	0.002Kg	---
SG2-15-N-5	1-55-19-12-00-SG2	15	26	M5	7	ASG-42-5	3,5N	NBR	0.002Kg	---
SG2-15-N-18	1-55-19-13-00-SG2	15	26	G1/8	7	ASG-70-18	3,5N	NBR	0.005Kg	---
SG2-20-N-5	1-55-19-35-00-SG2	20	28	M5	8,5	ASG-49-5	7,7N	NBR	0.006Kg	
SG2-20-N-18	1-55-19-36-00-SG2	20	28	G1/8	8,5	ASG-48-18	7,7N	NBR	0.007Kg	
SG2-30-N-18	1-55-19-55-00-SG2	30	37,5	G1/8	11,5	ASG-48-18	19,2N	NBR	0.012Kg	4
SG2-40-N-18	1-55-19-63-00-SG2	40	45	G1/8	10	ASG-48-18	28N	NBR	0.018Kg	4
SG2-40-N-14	1-55-19-64-00-SG2	40	37,5	G1/4	10	ASG-82-14	28N	N	0.012Kg	4
SG2-50-N-18	1-55-19-74-00-SG2	50	50	G1/8	18	ASG-50-18	59N	NBR	0.018Kg	5
SG2-50-N-14	1-55-19-75-00-SG2	50	50	G1/4	18	ASG-80-14	59N	NBR	0.018Kg	5
SG2-75-N-14	1-55-19-93-00-SG2	75	57	G1/4	17	ASG-52-14	152N	NBR	0.089Kg	5


Legend: L = Suction pad stroke M = Adapter N = holding force with 2-fold safety and 90% vacuum holding force 10N = 1kg O = Material (see legend)

SG2 / VACUUM CUP 2 EDGE (COMPLETE)

SG2-P Vacuum Cup with 2 Bellows (complete) PU







ADVANTAGES

- V1 - Suction on curved surfaces
- V2 - extremely light (aluminium adapter)
- V3 - All adapters with hexagon socket
- V4 - Quick assembly

REMARK

- To protect the material, all suction pads are only fitted with the adapter on request.
- Availability is guaranteed.
- Adapter with internal thread on request
- Scope of delivery:
- Adapter ASG and pneumatic sealing ring PDR

INFO

- Material: polyurethane elastomer PU
- Colour: light brown
- Shore hardness: 65 to 95 Shore A
- Temperature resistance: -40°C to +80°C,
- briefly up to 130°C
- Flexibility: *
- Abrasion resistance: ***
- Resistance to oil: **
- Compatibility with food: -
- Area of application: for harsh environmental conditions

DESIGNATION	ITEM NO.	A	B	C	L	M	N	O	SW	WEIGHT
SG2-20-P-5	1-55-29-22-00-SG2	20	28	M5	9	ASG-49-5	24N	PU	2	0.005Kg
SG2-30-P-18	1-55-29-26-00-SG2	30	36	G1/8	11	ASG-48-18	41N	PU	4	0.011Kg
SG2-50-P-18	1-55-29-34-00-SG2	50	43	G1/8	13,5	ASG-59-18	105N	PU	5	0.022Kg

Legend: L = Suction pad stroke M = Adapter N = holding force with 1-fold safety (-0.7bar) Holding force 10N = 1kg O = Material (see legend)