


SG2 / VACUUM CUP 2 EDGE (COMPLETE)

SG2-PU-EH-LC Vacuum Cup with 2 Bellow polyurethane compl one hardness







ADVANTAGES

- V1 - these PU suction cups are made with single hardening from a
- specially developed polyurethane. This material
- combines the elasticity of rubber with the holding power of plastic
- V2 - Key features are good elasticity and
- flexibility, high tensile strength with high wear resistance
- V3 - Virtually silicone and impression-free

REMARK

- Scope of delivery:
- including adapter and seal

INFO

- Material: PU specially developed polyurethane with single hardness
- Shore hardness:
- yellow suction cup: 40 °Shore
- Temperature resistance: 10°C to +50°C
- Flexibility: **
- Wear resistance: ***
- Resistance to oil: ***
- Compatibility with food: -

DESIGNATION	ITEM NO.	A	B	C	K	L	M	N	O	WEIGHT
SG2-10-PU-EH-40-5-LC	1-57-78-46-00-SG2	11	22,5	M5	40	4	ASG-150-5	1,6N	PU	0.003Kg
SG2-10-PU-EH-40-18-LC	1-57-78-47-00-SG2	11	22,5	G1/8	40	4	ASG-152-18	1,6N	PU	0.005Kg
SG2-15-PU-EH-40-5-LC	1-57-78-50-00-SG2	16	25,5	M5	40	5	ASG-150-5	3,8N	PU	0.004Kg
SG2-15-PU-EH-40-18-LC	1-57-78-51-00-SG2	16	25,5	G1/8	40	5	ASG-152-18	3,8N	PU	0.006Kg
SG2-20-PU-EH-40-18-LC	1-57-78-56-00-SG2	21	24,5	G1/8	40	6	ASG-202-18-LC	5,9N	PU	0.006Kg
SG2-30-PU-EH-40-18-LC	1-57-78-61-00-SG2	31,5	27,5	G1/8	40	6	ASG-203-18-LC	15,7N	PU	0.012Kg
SG2-30-PU-EH-40-14-LC	1-57-78-62-00-SG2	31,5	25,5	G1/4	40	6	ASG-204-14-LC	15,7N	PU	0.012Kg
SG2-40-PU-EH-40-18-LC	1-57-78-67-00-SG2	42	33	G1/8	40	8	ASG-203-18-LC	26,8N	PU	0.019Kg
SG2-40-PU-EH-40-14-LC	1-57-78-68-00-SG2	42	31	G1/4	40	8	ASG-204-14-LC	26,8N	PU	0.019Kg
SG2-50-PU-EH-40-18-LC	1-57-78-72-00-SG2	52,5	44	G1/8	40	12	ASG-207-18-LC	40N	PU	0.032Kg
SG2-50-PU-EH-40-14-LC	1-57-78-73-00-SG2	52,5	44	G1/4	40	12	ASG-205-14-LC	40N	PU	0.03Kg
SG2-50-PU-EH-40-14-LC	1-57-78-74-00-SG2	52,5	44	G3/8	40	12	ASG-206-38-LC	40N	PU	0.038Kg
SG2-70-PU-EH-40-38-LC	1-57-78-80-00-SG2	73	47	G3/8	40	13	-	76N	PU	0.062Kg

Legend: K = degree of hardness lip and bellows °Shore A M = adapter N = Holding force (vertical lifting direction) at vacuum -0.6 bar, 2-fold safety, holding force 10N = 1kg O = Material (see legend)