

SG2 / VACUUM CUP 2 EDGE (COMPLETE)

SG2-PU-ZH-LC Vacuum Cup with 2 Bellows polyurethane compl two hardness







ADVANTAGES

- V1 - the bellows and the lip have different degrees of hardness. This makes them strong and stable and
- equally soft and flexible: body 60 Shore /
- suction lip 30 Shore
- V2 - these suction cups are made from a specially
- developed polyurethane. This material combines the elasticity of rubber with the holding power
- of plastic
- V3 - Virtually silicone and impression-free
- V4 - excellent sealing properties

REMARK

- Suction pads with a diameter of 10 mm are manufactured with a single hardening (60 ° Shore A)
- Scope of delivery:
- incl. ASG adapter and pneumatic seal

INFO

- Material: Polyurethane (PU)
- Shore hardness: lip 30 °Shore A, bellows 60 °Shore A
- Temperature resistance: 10°C to +50°C
- Flexibility: ***
- Wear resistance: ***
- Resistance to oil: ***
- Compatibility with food: -

DESIGNATION	ITEM NO.	A	B	C	J	K	L	M	N	O	WEIGHT
SG2-10-PU-ZH-60-5-LC	1-57-70-46-00-SG2	11	22,5	M5	-	60	6	ASG-150-5	1,3N	PU	0.003Kg
SG2-10-PU-ZH-60-18-LC	1-57-70-47-00-SG2	11	22,5	G1/8	-	60	6	ASG-152-18	1,3N	PU	0.005Kg
SG2-15-PU-ZH-30-60-5-LC	1-57-70-50-00-SG2	16	25	M5	30	60	6	ASG-150-5	3,5N	PU	0.004Kg
SG2-15-PU-ZH-30-60-18-LC	1-57-70-51-00-SG2	16	25	G1/8	30	60	6	ASG-152-18	3,5N	PU	0.006Kg
SG2-20-PU-ZH-30-60-18-LC	1-57-70-56-00-SG2	21	24,5	G1/8	30	60	9	ASG-202-18	5,7N	PU	0.006Kg
SG2-30-PU-ZH-30-60-18-LC	1-57-70-61-00-SG2	31,5	27,5	G1/8	30	60	9	ASG-203-18	15N	PU	0.012Kg
SG2-30-PU-ZH-30-60-14-LC	1-57-70-62-00-SG2	31,5	25,5	G1/4	30	60	9	ASG-204-14	15N	PU	0.012Kg
SG2-40-PU-ZH-30-60-18-LC	1-57-70-67-00-SG2	42	33	G1/8	30	60	11	ASG-203-18	25N	PU	0.019Kg
SG2-40-PU-ZH-30-60-14-LC	1-57-70-68-00-SG2	42	31	G1/4	30	60	11	ASG-204-14	25N	PU	0.019Kg
SG2-50-PU-ZH-30-60-18-LC	1-57-70-72-00-SG2	52,5	40	G1/8	30	60	12	ASG-207-18	40N	PU	0.032Kg
SG2-50-PU-ZH-30-60-14-LC	1-57-70-73-00-SG2	52,5	40	G1/4	30	60	12	ASG-205-14	40N	PU	0.03Kg
SG2-50-PU-ZH-30-60-38-LC	1-57-70-74-00-SG2	52,5	40	G3/8	30	60	12	ASG-206-38	40N	PU	0.038Kg
SG2-70-PU-ZH-30-60-38-LC	1-57-70-80-00-SG2	73	45	G3/8	30	60	17	---	78N	PU	0.062Kg

Legend: J = Lip hardness °Shore A K = Bellows hardness °Shore A L = Suction pad stroke M = ASG adapter N = Holding force (vertical lifting direction) at vacuum -0.6 bar, 2-fold safety, holding force 10N = 1kg O = Material (see legend)

SG2 / VACUUM CUP 2 EDGE (COMPLETE)

SG2-N-SCH Suction pad 2 edges with foam lip (complete)



