

DESIGNATION	ITEM NO.	A	C	D	E	L	M	N	B
SG2-20-N-18-SCH	1-55-50-08-00-SG2	20	G1/8	16	3	6,5	14N	7N	
SG2-25-N-18-SCH	1-55-50-14-00-SG2	26	G1/8	24,5	3	10	23N	11,5N	
SG2-33-N-18-SCH	1-55-50-20-00-SG2	33	G1/8	27,5	5	11	39N	19,5N	39,5

SG3 / VACUUM CUP 3 EDGE (COMPLETE)

SG3 Vacuum Cup with 3 Bellows (complete)







ADVANTAGES

- V1 - Suction on curved surfaces
- V2 - extremely light (aluminium adapter)
- V3 - All adapters with hexagon socket
- V4 - Quick assembly

REMARK

- To protect the material, all suction pads are only fitted with the adapter on request.
- Availability is guaranteed.
- Adapter with internal thread on request
- Scope of delivery:
- Adapter ASG and pneumatic sealing ring PDR

INFO

- Material: Nitrile (NBR)
- Colour: black
- Shore hardness: 60 +/- 5
- Temperature resistance: -0°C to 80°C
- Flexibility: *
- Abrasion resistance: *
- Resistance to oil: **
- Compatibility with food: -
- Material: High-performance elastomer (HE)
- Colour: blue
- Shore hardness: 60 +/- 5
- Temperature resistance: -20°C to 150°C
- Flexibility: *
- Abrasion resistance: **
- Resistance to oil: **
- Compatibility with food: -
- Area of application: Painting of plastic parts,
- leaves no imprint
- For optimum impression behaviour, please clean the
- absorbent surfaces with a lint-free cloth
- and acetone

DESIGNATION	ITEM NO.	A	B	C	L	M	N	O	WEIGHT	SW
SG3-5-S-5	1-55-22-11-00-SG3	5	19	M5	3	ASG-42-5	0,66N	S	0.001Kg	
SG3-5-HE-5	1-55-22-13-00-SG3	5	19	M5	3	ASG-42-5	0,66N	HE	0.001Kg	2
SG3-7-S-5	1-55-22-16-00-SG3	7	19	M5	3	ASG-42-5	1,3N	S	0.001Kg	2
SG3-7-HE-5	1-55-22-18-00-SG3	7	19	M5	3	ASG-42-5	1,3N	HE	0.001Kg	2
SG3-9-S-5	1-55-22-22-00-SG3	9	21	M5	3	ASG-54-5	1,5N	S	0.002Kg	2
SG3-9-S-18	1-55-22-23-00-SG3	9	21	G1/8	3	ASG-55-18	1,5N	S	0.004Kg	3
SG3-9-HE-5	1-55-22-27-00-SG3	9	21	M5	3	ASG-54-5	1,5N	HE	0.002Kg	2
SG3-9-HE-18	1-55-22-28-00-SG3	9	21	G1/8	3	ASG-55-18	1,5N	HE	0.004Kg	3
SG3-14-S-5	1-55-22-32-00-SG3	14	32	M5	8,5	ASG-54-5	4,1N	S	0.003Kg	2
SG3-14-S-18	1-55-22-33-00-SG3	14	32	G1/8	8,5	ASG-55-18	4,1N	S	0.005Kg	3
SG3-14-HE-5	1-55-22-36-00-SG3	14	32	M5	9,5	ASG-54-5	4,1N	HE	0.003Kg	2
SG3-14-HE-18	1-55-22-37-00-SG3	14	32	G1/8	8,5	ASG-55-18	4,1N	HE	0.005Kg	3
SG3-18-S-5	1-55-22-42-00-SG3	18	32	M5	10	ASG-54-5	6,1N	S	0.003Kg	2