

DESIGNATION	ITEM NO.	A	B	C	J	K	L	M	N	O	WEIGHT
SG3-50-PU-ZH-30-60-38-LC	1-57-70-30-00-SG3	50	46,5	G3/8	30	60	17	ASG-206-38	40N	PU	0.032Kg
SG3-70-PU-ZH-30-60-38-LC	1-57-70-34-00-SG3	70	46,5	G3/8	30	60	25	-	60N	PU	0.059Kg


Legend: J = Lip hardness °Shore A K = Bellows hardness °Shore A L = Suction pad stroke M = ASG adapter N = Holding force (vertical lifting direction) at vacuum -0.6 bar, 2-fold safety, holding force 10N = 1kg O = Material (see legend)

SG3 / VACUUM CUP 3 EDGE (COMPLETE)

SG3-PU-ZH-FL-LC Vacuum Cup with 3 Bellows polyurethane compl 2 hardness flexible lip







ADVANTAGES

- V1 - the bellows and the lip have different degrees of hardness.
- This gives them a secure and stable grip but also
- soft and flexible: body 55 Shore / suction lip 30 Shore
- V2 - these suction pads are made from a specially developed
- polyurethane. This material combines the elasticity
- of rubber with the holding power of plastic
- V3 - Virtually silicone and impression-free
- V4 - excellent sealing properties

REMARK

- Scope of delivery:
- incl. ASG adapter and pneumatic seal

INFO

- Material: Polyurethane (PU)
- Shore hardness: lip 30 °Shore A, bellows 55 °Shore A
- Temperature resistance: 5°C to +50°C
- Flexibility: ***
- Wear resistance: ***
- Resistance to oil: ***
- Compatibility with foodstuffs: -

DESIGNATION	ITEM NO.	A	B	C	J	K	L	M	N	O	WEIGHT
SG3-25-PU-30-55-18-LC	1-57-80-08-00-SG3	25	22	G1/8	30	55	6,5	ASG-202-18-LC	8,2N	PU	0.006Kg
SG3-35-PU-ZH-30-55-18-FL-LC	1-57-80-12-00-SG3	35	29	G1/8	30	55	10	ASG-202-18-LC	14,7N	PU	0.008Kg
SG3-45-PU-ZH-30-55-18-FL-LC	1-57-80-18-00-SG3	45	39,5	G1/8	30	55	15	ASG-203-18-LC	23N	PU	0.018Kg
SG3-45-PU-ZH-30-55-14-FL-LC	1-57-80-20-00-SG3	45	37,5	G1/4	30	55	15	ASG-ASG-204-14	23N	PU	0.018Kg
SG3-55-PU-ZH-30-55-18-FL-LC	1-57-80-24-00-SG3	53,6	47,5	G1/8	30	55	17	ASG-207-18-LC	35N	PU	0.032Kg
SG3-55-PU-ZH-30-55-14-FL-LC	1-57-80-26-00-SG3	53,6	47,5	G1/4	30	55	17	ASG-205-14-LC	35N	PU	0.03Kg
SG3-55-PU-ZH-30-55-38-FL-LC	1-57-80-28-00-SG3	53,6	47,5	G3/8	30	55	17	ASG-206-38-LC	35N	PU	0.038Kg

Legend: J = Lip hardness °Shore A K = Bellows hardness °Shore A L = Suction pad stroke M = ASG adapter N = Holding force (vertical lifting direction) at vacuum -0.6 bar, 2-fold safety, holding force 10N = 1kg O = Material (see legend)