

GRIPPER 2 PISTONS

GZA-S Gripper with Saw Tooth Jaws







ADVANTAGES

- V1 - Closing movement via 2 pistons
- V2 - Gripper jaws with special coating
- V3 - compact attachment/ optimised force transmission
- -short levers
- V4 - Gripper jaws with saw tooth
- V5 - Clamping diameter (A) usable over the entire
- length

REMARK

- Operating principle: Single-acting
- Operating pressure: 6 bar filtered and dried
- air
- The image above shows our GZA-14-16-S gripper.


DESIGNATION	ITEM NO.	A	B	C	D	E	F	M	N	WEIGHT	X
GZA-10-8-S	1-60-08-16-00-GZA	10	8	41	M5	12,3	M5	P13	12N	0.015Kg	0,5-3mm
GZA-10-12-S	1-60-10-16-00-GZA	10	19	68	M5	17,5	M5	P13	20N	0.04Kg	1,5-6mm
GZA-14-16-S	1-60-12-16-00-GZA	14	21	75	M5	22,5	M5	P13	55N	0.077Kg	2,5-8mm
GZA-20-20-S	1-60-14-16-00-GZA	20	25	85	M5	29	M5	P22	100N	0.148Kg	3,5-12


Legend: D = Air connection through shaft F = lateral air connection N = gripping force (at 6 bar) X = suitable for sprue thickness ... Gripping force 10N = 1kg

GRIPPER 2 PISTONS

GZA-G Gripper with Smooth Jaws







ADVANTAGES

- V1 - Closing movement via 2 pistons
- V2 - Gripper jaws with special coating
- V3 - compact attachment/ optimised force transmission
- -short levers
- V4 - Gripper jaws with smooth surface
- V5 - Clamping diameter (A) usable over the entire
- length

REMARK

- Operating principle: Single-acting
- Operating pressure: 6 bar filtered and dried
- air
- The illustration above shows our GZA-14-16-G gripper.

DESIGNATION	ITEM NO.	A	B	C	D	E	F	M	N	WEIGHT	X
GZA-10-8-G Gripper with Smooth Jaws	1-60-08-18-00-GZA	10	8	41	M5	12,3	M5	P13	12N	0.015Kg	0,5-3mm
GZA-10-12-G	1-60-10-18-00-GZA	10	19	68	M5	17,5	M5	P13	20N	0.04Kg	1,5-6mm
GZA-14-16-G	1-60-12-18-00-GZA	14	21	75	M5	22,5	M5	P13	55N	0.077Kg	2,5-8mm
GZA-20-20-G	1-60-14-18-00-GZA	20	25	85	M5	29	M5	P22	100N	0.148Kg	3,5-12

Legend: D = Air connection through shaft F = lateral air connection N = gripping force (at 6 bar) X = suitable for sprue thickness ... Gripping force 10N = 1kg