

GRIPPER 2 PISTONS

GZA-L Gripper with Holes in Jaws







ADVANTAGES

- V1 - Closing movement via 2 pistons
- V2 - Gripper jaws with special coating
- V3 - compact attachment/ optimised force transmission
- -short levers
- V4 - Clamping diameter (A) usable over the entire
- length

REMARK

- Operating principle: Single-acting
- Operating pressure: 6 bar filtered and dried
- air
- The illustration above shows our GZA-14-16-L gripper.


DESIGNATION	ITEM NO.	A	B	C	D	E	F	K	N	WEIGHT	X
GZA-10-12-L	1-60-10-30-00-GZA	10	18	68,5	M5	17,5	M5	P13	20N	0.038Kg	1,5-6mm
GZA-14-16-L	1-60-12-30-00-GZA	14	18	75	M5	22,5	M5	P13	55N	0.078Kg	2,5-8mm
GZA-20-20-L	1-60-14-30-00-GZA	20	22	85	M5	29	M5	P22	100N	0.142Kg	3,5-12mm


Legend: D = Air connection through shaft F = lateral air connection N = gripping force (at 6 bar) X = suitable for sprue thickness ... Gripping force 10N = 1kg

GRIPPER 2 PISTONS

GZA-P Gripper with Polyurethan Inserts







ADVANTAGES

- V1 - Closing movement via 2 pistons
- V2 - Gripper jaws with polyurethane insert
- V3 - compact attachment/ optimised force transmission
- -short levers
- V4 - Clamping diameter (A) usable over the entire
- length

REMARK

- Operating principle: Single-acting
- Operating pressure: 6 bar use filtered and dried
- air
- Optional: Query
- PU coating hardness: 55° Shore A
- Temperature resistance: 80°C
- The image above shows our GZA-14-16-P gripper.

DESIGNATION	ITEM NO.	A	B	C	D	E	F	K	N	WEIGHT	X
GZA-10-12-P	1-60-10-32-00-GZA	10	18	68,5	M5	17,5	M5	P13	20N	0.04Kg	1,5-6mm
GZA-14-16-P	1-60-12-32-00-GZA	14	18	75	M5	22,5	M5	P13	55N	0.083Kg	2,5-8mm
GZA-20-20-P	1-60-14-32-00-GZA	20	22	85	M5	29	M5	P22	100N	0.158Kg	3,5-12mm

Legend: D = Air connection through shaft F = lateral air connection N = gripping force (at 6 bar) X = suitable for sprue thickness ... Gripping force 10N = 1kg