

GRIPPER 2 PISTONS

GZA-G-T Gripper with Smooth Teflon Coated Jaws







ADVANTAGES

- V1 - the smooth gripper jaws are Teflon-coated. Thus
- the sprue cannot stick to the jaws
- V2 - Closing movement via 2 pistons
- V3 - compact fastening / optimum force transmission
- -short levers
- V4 - Clamping diameter (A) usable over the entire length

REMARK

- Operating principle: Single-acting
- Operating pressure: 6 bar use filtered and dried
- air
- The image above shows our GZA-14-16-G-T gripper.


DESIGNATION	ITEM NO.	A	B	C	D	E	F	M	N	WEIGHT	X
GZA-10-12-G-T	1-60-10-48-00-GZA	10	19	68	M5	17,5	M5	P13	20N	0.04Kg	1,5-6mm
GZA-14-16-G-T	1-60-12-48-00-GZA	14	21	75	M5	22,5	M5	P13	55N	0.04Kg	2,5-8mm
GZA-20-20-G-T	1-60-14-48-00-GZA	20	25	85	M5	29	M5	P22	100N	0.04Kg	3,5-12mm


Legend: D = Air connection through shaft F = lateral air connection N = gripping force (at 6 bar) Gripping force 10N = 1kg X = suitable for sprue thickness ...

GRIPPER 2 PISTONS

GZA-EP Gripper with Elastomer-PUR Coating







ADVANTAGES

- V1 - the gripper jaws have a high-strength elastomer-PUR coating.
- V2 – can be used to grip workpieces made from a wide variety of materials without causing damage
- V3 - the jaws are abrasion-resistant and very grippy due to the high static friction
- V4 - compact attachment/optimised force transmission
- -short levers
- V5 - heat-resistant up to 130°C for short periods

REMARK

- Operating principle: Single-acting
- Operating pressure: 6 bar Use filtered and dried air

DESIGNATION	ITEM NO.	A	B	C	D	E	F	M	N	WEIGHT	X
GZA-10-12-EP	1-60-10-38-00-GZA	10	19	68	M5	17,5	M5	P13	20N	0.04Kg	1,5-6mm
GZA-14-16-EP	1-60-12-38-00-GZA	14	21	75	M5	22,5	M5	P13	55N	0.077Kg	2,5-8mm
GZA-20-20-EP	1-60-14-38-00-GZA	20	25	85	M5	29	M5	P22	100N	0.148Kg	3,5-12mm

Legend: D = Air connection N = gripping force (at 6 bar) Gripping force 10N = 1kg X = suitable for sprue thickness ...