

63.0 Parallel Grippers




PARALLEL GRIPPER EASY

PAG-E Parallel Gripper easy







ADVANTAGES

- V1 - Query gripper open or closed with favourable standard C-slot cylinder sensor ZYS-4-H6-500-S possible
- V2 - Robust design


REMARK


- Operating principle: Double-acting
- Operating pressure: 6 bar filtered and dried air
- Use
- Mounting option: Adapter for parallel gripper
- easy APG-E
- Order cylinder sensor ZYS-4-H6-500-S separately
- Optional: Cover for guide


DESIGNATION	ITEM NO.	A	B	C	D	E	F	K	L	M	N	O	WEIGHT
PAG-6-E	1-60-80-20-00-PAG	10	20	53	12	5	8	M2	2	3,3N	M3	6,1N	0.027Kg
PAG-10-E	1-60-80-22-00-PAG	16	23	57	15,2	5,7	11,2	M2,5	2	11N	M3	17N	0.055Kg
PAG-16-E	1-60-80-24-00-PAG	24	30	67	21	7	15	M3	3	34N	M5	45N	0.115Kg
PAG-20-E	1-60-80-26-00-PAG	28	42	85	26,3	9	16,3	M4	5	42N	M5	66N	0.235Kg
PAG-25-E	1-60-80-28-00-PAG	34	52	103	33,3	12	19,3	M5	7,0	65N	M5	104N	0.43Kg

PARALLEL GRIPPER EASY

PAG-E-EW-DG Parallel Gripper Easy single-acting, opened without pressure







ADVANTAGES

- V1 - Query gripper open or closed with favourable standard C-slot cylinder sensor ZYS-4-H6-500-S possible
- V2 - Robust design

DESIGNATION	ITEM NO.	A	B	C	D	E	F	K	L	M	N	WEIGHT
PAG-6-E-EW-DG	1-60-80-20-00-002	10	20	53	12	5	8	M2	2	1,9N	M3	0.027Kg
PAG-10-E-EW-DG	1-60-80-22-00-002	16	23	57	15,2	5,7	11,2	M2,5	2	7,1N	M3	0.055Kg
PAG-16-E-EW-DG	1-60-80-24-00-002	24	30	67	21	7	15	M3	3	27N	M5	0.115Kg