
GRIPPER FINGER ROUND

GFI-95-E-VA Gripper Finger 95° Easy made from stainless steel





ADVANTAGES

- V1 - Fingers and head made of stainless steel
- V2 - very short design
- V3 - favourable gripper finger
- V4 - various mounting options
- V5 - Marking aid every 10mm on shaft for
- easy adjustment
- V6 - Pre-centred for pressure plate Easy DRP-X-E-G

REMARK

- Operating principle: Single-acting
- - Extension thread for extension tube VLR
- - Query option
- Operating pressure: 6 bar filtered and dried air


DESIGNATION	ITEM NO.	A	B	C	D	M	N	WEIGHT	X
GFI-20-95-E-VA	1-65-03-10-00-GFI	20	M17×1	83	5	40N	M5	0.075Kg	DRP-16-X-E-G


Legend: D = here pre-centred for pressure plate Easy DRP-X-E-G Ø through-hole for DRP-X-E-G E = Basic finger position F = Finger extended G = maximum opening angle M = gripping force (at 6 bar) Gripping force 10N = 1kg N = Air connection X = suitable for DRP-X-E-G

GRIPPER FINGER ROUND

GFI-35-E Gripper Finger 35° Easy







ADVANTAGES

- V1 - very short design
- V2 - favourable gripper finger
- V3 - various mounting options
- V4 - Marking aid every 10 mm on the shaft for
- easy adjustment

REMARK

- Operating principle: Single-acting
- - Extension thread for extension tube VLR
- - Query option as an option
- Operating pressure: 6 bar filtered and dried
- air

DESIGNATION	ITEM NO.	A	B	C	M	N	WEIGHT
GFI-14-35-E	1-65-00-12-00-GFI	14	M12×1	56	20N	M5	0.017Kg
GFI-20-35-E	1-65-02-12-00-GFI	20	M17×1	74	45N	M5	0.049Kg
GFI-30-35-E	1-65-04-12-00-GFI	30	M27×1	104	125N	G1/8	0.141Kg

Legend: E = Basic finger position F = Finger extended G = maximum opening angle M = gripping force (at 6 bar) Gripping force 10N = 1kg N = Air connection