


# 86.0 Rotary units



## DRZ-LC Rotary cylinder






**ADVANTAGES**

- V1 - Angle of rotation adjustable from 0° to X
- V2 - Standard mounting options

**REMARK**


- Operating principle: Double-acting
- Operating pressure: 6bar filtered and dried air
- use


| DESIGNATION | ITEM NO. | A | B | E | I | N | O | WEIGHT |
|---|---|---|---|---|---|---|---|---|
| **DRZ-10-LC** | 1-80-98-10-00-DRZ | 38 | 25 | 180° | 10 | M3 | 0,14Nm | 0.146Kg |
| **DRZ-15-LC** | 1-80-98-12-00-DRZ | 44 | 30 | 180° | 15 | M5 | 0,38Nm | 0.229Kg |

**Legend:** E = max angle of rotation I = piston diameter N = Air connection O = Torque in Nm

## ADA-DRZ-P Adapter plate for rotary cylinder with prism





**ADVANTAGES**

- V1 - this allows the DRZ-LC rotary unit to be
- easily integrated into the PreciGrip system
- system

**REMARK**

- Material: Aluminium
- Scope of delivery:
- incl. mounting material

| DESIGNATION | ITEM NO. | A | B | WEIGHT | X |
|---|---|---|---|---|---|
| **ADA-DRZ-10-P22** | 1-80-99-10-00-ADA | P22 | 27 | 0.038Kg | DRZ-10-LC |
| **ADA-DRZ-15-P22** | 1-80-99-12-00-ADA | P22 | 29 | 0.04Kg | DRZ-15-LC |

**Legend:** X = suitable for ...