
DESIGNATION	ITEM NO.	A	B	WEIGHT
PWS-5-4-S	1-90-10-02-18-PWS	PSC-4	M5	0.003Kg
PWS-5-6-S	1-90-10-02-20-PWS	PSC-6	M5	0.003Kg
PWS-18-4-S	1-90-10-02-22-PWS	PSC-4	G1/8	0.003Kg
PWS-18-6-S	1-90-10-02-24-PWS	PSC-6	G1/8	0.003Kg

Legend: A = suitable for pneumatic hose ... B = connection thread

90.2 - QUICK CONNECTOR WITH THREAD

PWS-L Pneumatic L Hose Connector Large Version





ADVANTAGES
- V1 - optimal hose connection
- V2 - self-sealing thread
- V3 - quick push-fit connection
- V4 - rotatable


DESIGNATION	ITEM NO.	A	B	C
PWS-L-4-M5	1-90-60-30-00-PWS	PSC-4	M5	28,9
PWS-L-4-18	1-90-60-32-00-PWS	PSC-4	1/8	25,5
PWS-L-6-M5	1-90-60-35-00-PWS	PSC-6	M5	33,5
PWS-L-6-18	1-90-60-37-00-PWS	PSC-6	1/8	32

Legend: A = suitable for pneumatic hose ... B = Connection thread

90.2 - QUICK CONNECTOR WITH THREAD

SVY-2SA Pneumatic Y push-in fitting with 2 push-in connections





ADVANTAGES
- V1 - optimum hose connection
- V2 - self-sealing thread
- V3 - quick push-in connection
- V4 - rotatable


DESIGNATION	ITEM NO.	A	B
SVY-2SA-6-18	1-90-60-10-00-SVY	PSC-4	1/8
SVY-2SA-6-18	1-90-60-13-00-SVY	PSC-6	1/8

Legend: A = suitable for pneumatic hose ... B = Connection thread

90.2 - QUICK CONNECTOR WITH THREAD

SVY-4SA Pneumatic Y push-in fitting with 4 push-in connections





ADVANTAGES
- V1 - optimum hose connection
- V2 - self-sealing thread
- V3 - quick push-in connection
- V4 - rotatable

DESIGNATION	ITEM NO.	A	B
SVY-4SA-4-18	1-90-60-90-00-SVY	PSC-4	1/8