
DESIGNATION	ITEM NO.	A	B	WEIGHT
MVE-90-12-A-C-STW	1-90-00-10-21-MVE	PSC6	G1/4	0.118Kg

MVE-SI-I Modular vacuum generator inline





ADVANTAGES

- V1 - Patented COAX® cartridge technology
- V2 - High suction power in relation to
- energy consumption
- V3 - Low weight, inline design with
- plug-in connection for vacuum and compressed air
- V4 - Quick and easy installation directly
- on the hose

INFO

- Material:
- PA, NBR, SS, CuZn, Al*
- *only MVI-I-SI-6-6
- Material:
- PA, NBR, SS, CuZn, Al*
- *only MVI-I-SI-6-6

OPTION


- Various suction capacities and feed pressures
- Silencer

DESIGNATION	ITEM NO.	A	B	C	D	E	F	G	H	I
MVE-SI-I-6-6-70	1-92-00-08-00-MVE	6	6	-10° + 80°	6	0,12	75	0,28	67-73	70
MVE-SI-I-6-6	1-92-00-10-00-MVE	6	6	-10° + 80°	6	0,44	75	0,69	68-84	98
MVE-SI-I-8-12	1-92-00-12-00-MVE	8	12	-10°C + 80°C	6	1,75	75	3,1	90-98	155

Legend: A = 1 - Air connection B = 2 - Vacuum connection C = Temperature resistance D = optimum feed pressure bar E = Air consumption NL/s F = max. ultimate vacuum -kPa G = max. volume flow Nl/s at 0% H = Noise level dBA

VPU-SI-M-1D Vacuum pump midi 1 injection tube





ADVANTAGES

- V1 - Patented COAX® cartridge technology
- V2 - Contains a flow silencer that is not affected by dust or dirt
- V3 - Significantly lower air consumption compared to conventional pumps of the same size
- V4 - Slim, compact, customisable module design
- V5 - low weight

INFO

- Material:
- PP, PA, NBR, Al, SS
- Material: PP, PA, NBR, Al, SS

OPTION

- Other nozzles with different suction power and feed pressure

DESIGNATION	ITEM NO.	A	B	C	D	E	F	G	H	I	J
VPU-SI-10-M	1-92-10-40-00-VPU	Ø10	G1/8	G1/8	G1/2	-10°C + 80°C	6	1,75	75	6	68-70

Legend: A = 1 - Air connection Ø10 B = 1 - Air connection G1/8 C = 1 - Vacuum connection G1/8 D = 1 - Vacuum connection G1/2 E = Temperature resistance F = optimum feed pressure bar G = Air consumption NL/s H = max. ultimate vacuum -kPa I = max. volume flow Nl/s at 0% J = Noise level dBA