

SENSOR

ZYS-3.7-S-90 Cylinder sensor with plug 90°







ADVANTAGES

- V1 - suitable for 4mm C-slot
- V2 - quick and easy insertion of the sensor
- from above into the groove
- V3 - 90° rotated cable connection
- V4 - very short housing

INFO


- Description:
- - 500mm cable with M8 3-pin plug
- - PNP switching output
- - 90° mounting & cable outlet
- - LED for signal control
- - Ambient temperatures from -30°C to +80°C
- Links:
- MPZ - Parallel gripper

DESIGNATION	ITEM NO.	A	B	WEIGHT
ZYS-3,7-500-S	1-97-03-10-00-ZYS	3,7	12,2	0.01Kg

SENSOR

ZYS-4 Cylinder sensor with plug





ADVANTAGES

- V1 - suitable for 4mm C groove
- V2 - Clamping via grub screw

INFO


- Description:
- - 300mm cable with M8 3-pin plug
- - PNP switching output
- - LED for signal control
- - Ambient temperatures from -20°C to +70°C
- On the left:
- Application examples connection components

DESIGNATION	ITEM NO.	A	B	C	WEIGHT
ZYS-4-300-S	1-97-02-16-00-ZYS	3	5	M8	0.01Kg

SENSOR

ZYS-4-H6-500-S Cylinder sensor with plug





ADVANTAGES

- V1 – variable suitable for 4mm C-slot and when using the holder suitable for 6mm slot

INFO

- Description:
- - 500mm 3-wire cable
- - PNP switching output
- - LED for signal control
- - Ambient temperatures from -10°C to +60°C
- Links:
- Application examples of connection components

DESIGNATION	ITEM NO.	A	B	WEIGHT
ZYS-4-H6-500-S	1-97-03-50-00-ZYS	4	6	0.011Kg