
SENSOR

ZYS-3.6-K-KSF Cylinder sensor with cable short-circuit proof





ADVANTAGES

- V1 - Short-circuit proof
- V2 - Reverse polarity protected
- V3 - Stainless steel housing
- V4 - suitable for 4mm C slot
- V5 - Clamping via grub screw

REMARK

- - 2000mm cable with open cable end
- - PNP switching output
- 10-30V DC, 1x PNP 100mA, 500Hz
- - LED for signal control
- - Ambient temperatures from -25°C to +85°C

INFO

- Links:
- KAD - cable socket
- GZA-C - Gripper
- GZA-S-C-S - Gripping tongs


DESIGNATION	ITEM NO.	A	B	D	E	WEIGHT
ZYS-3.6-2000-K-KSF	1-97-02-62-00-ZYS	3,6	2,9	2000	3-P	0.01Kg

Legend: D = Cable length E = X-pole

SENSOR

ZYS-3,7-S Cylinder sensor with plug





ADVANTAGES

- V1 - suitable for 4mm C slot
- V2 - metal housing
- V3 - Clamping via grub screw

INFO


- Description:
- - 300mm cable with M8 3-pin connector
- - PNP switching output
- - LED for signal control
- - Ambient temperatures from -20°C to +70°C
- Links:
- KAD - cable socket
- GZA-C - gripper
- GZA-S-C-S - gripping tongs

DESIGNATION	ITEM NO.	A	WEIGHT
ZYS-3,7-300-S	1-97-02-10-00-ZYS	3,7	0.017Kg

SENSOR

ZYS-3.6-S-KSF Cylinder sensor with plug short-circuit proof





INFO

- Links:
- KAD - cable socket
- GZA-C - Gripper
- GZA-S-C-S - Gripping tongs

DESIGNATION	ITEM NO.	A	B	C	D	E	WEIGHT
ZYS-3.6-300-S-KSF	1-97-02-60-00-ZYS	3,6	2,9	M8	3-P	300	0.01Kg