
DESIGNATION	ITEM NO.	A	B	C	D	WEIGHT
ATK-M-14-120	1-97-01-17-00-ATK	14	120	M2,5	25,4	0.044Kg

Legend: C = through thread

SENSOR HOLDER

HLT Holder for Proximity Switch





ADVANTAGES
- V1 - simple mounting of the cylinder sensor ZYS

REMARK
- HLT-ZYS-5-5 = variable clamping Ø
- HLT-18 = for standard cylinder Ø18

INFO
- Accessories:
- Link > 65 gripper fingers


DESIGNATION	ITEM NO.	A	C	D	WEIGHT
HLT-ZYS-5-5 Holder	1-97-02-32-00-HLT	8-25mm	ZYS-5-5	-	0.008Kg
HLT-14	1-97-02-38-00-HLT	14	ZYS-3,7	GFI-14	0.01Kg
HLT-18	1-97-02-39-00-HLT	18	ZYS-3,7	-	0.006Kg
HLT-20	1-97-02-40-00-HLT	20	ZYS-3,7	GFI-20	0.006Kg
HLT-30	1-97-02-42-00-HLT	30	ZYS-3,7	GFI-30	0.009Kg


Legend: C= suitable for cylinder sensor D - suitable for gripper finger GFI-...-E

SENSOR HOLDER

HLT-90 Holder for Proximity Switch 90°







ADVANTAGES
- V1 - simple 90° attachment of the ZYS cylinder sensor
- V2 - Holder HLT-90°, mounted on gripper finger GFI, enable
- Querying two positions using ZYS-3.7 sensors (2x)
- or ZYS-TE (1x)


DESIGNATION	ITEM NO.	A	B	C	D	E	F	WEIGHT
HLT-14-90°	1-97-03-38-00-HLT	14	90°	ZYS-3.7	ZVE-14	-	ZYS-TE-3.8-3-500-S	0.004Kg
HLT-20-90°	1-97-03-40-00-HLT	20	90°	ZYS-3.7	ZVE-20	GFI-20	ZYS-TE-3.8-3-500-S	0.007Kg
HLT-30-90°	1-97-03-42-00-HLT	30	90°	ZYS-3.7	ZVE-30	GFI-30	ZYS-TE-3.8-3-500-S	0.007Kg

Legend: B = Hole for sensor X° rotated to hole for operating element C = suitable for cylinder sensor ZYS-... D = suitable for centring unit ZVE-... E = suitable for gripping finger GFI-...-E F = suitable for teachable sensor ZYS-TE ....

SENSOR HOLDER

AIN receptacle for INS-S







DESIGNATION	ITEM NO.	A	B	C	D
AIN-M8-10	1-97-60-04-00-AIN	8	10	INS-M8-S	Ø10