
DESIGNATION	ITEM NO.	A	B	C	D	E	F	G	WEIGHT
KAV-M8-3P-1,0-M8	1-97-06-45-00-KAV	M8×1	3-polig	1,0m	M8×1	0,25mm²	32	39	0.016Kg
KAV-M8-4P-0,3-M8	1-97-06-60-00-KAV	M8×1	4-polig	0,3m	M8×1	0,25mm²	32	39	0.02Kg
KAV-M8-4P-0,5-M8	1-97-06-65-00-KAV	M8×1	4-polig	0,5m	M8×1	0,25mm²	32	39	0.02Kg
KAV-M8-4P-0,7-M8	1-97-06-70-00-KAV	M8×1	4-polig	0,7m	M8×1	0,25mm²	32	39	0.04Kg
KAV-M8-4P-0,7-M8	1-97-06-75-00-KAV	M8×1	4-polig	1,0m	M8×1	0,25mm²	32	39	0.04Kg

PLUG / CABLE

EST-3P Plug Connection 3 pin male





ADVANTAGES

- V1 - You determine the cable length of the KAD cable socket yourself
- V2 - optimal routing of the cable
- V3 - simple assembly
- V4 - the wires do not need to be soldered

REMARK

- M8 - 3 pole pin

INFO

- Links:
- EVE - Electrical distributor
- UVE - DUO distributor
- DVE - AND distributor
- Application examples for connection components


DESIGNATION	ITEM NO.	A	B	C	WEIGHT
EST-M8-3P-0.08-0,25mm²	1-97-00-30-00-EST	M8	3	0.08-0,25mm²	0.009Kg
EST-M8-3P-0.25-0,5mm²	1-97-00-31-00-EST	M8	3	0.25-0,5mm²	

Legend: B = xx -pole C = Connection cross-section min.-max.

PLUG / CABLE

EST-3D Plug Connection 3 pin female





ADVANTAGES

- V1 - You determine the cable length of the KAD cable socket yourself
- V2 - optimal routing of the cable
- V3 - simple assembly
- V4 - the wires do not need to be soldered

REMARK

- M8 - 3 pole socket

INFO

- Links:
- Application examples for connection components

DESIGNATION	ITEM NO.	A	B	C	WEIGHT
EST-M8-3D-0.08-0,25mm²	1-97-00-34-00-EST	M8	3	0.08-0,25mm²	0.009Kg
EST-M8-3D-0,25-0,5mm²	1-97-00-35-00-EST	M8	3	0,25-0,5mm²	

Legend: B = xx -pole C = Connection cross-section min.-max.