
PLUG / CABLE

## EST-4P Plug Connection 4 pin male






**ADVANTAGES**
- V1 - You determine the cable length of the KAD cable socket yourself
- V2 - optimal routing of the cable
- V3 - simple assembly
- V4 - the wires do not need to be soldered

**REMARK**
- - Available in M8 and M12

**INFO**
- Links:
- Application examples for connection components


| DESIGNATION | ITEM NO. | A | B | C | WEIGHT |
|---|---|---|---|---|---|
| **EST-M8-4P-0.08-0,25mm²** | 1-97-00-32-00-EST | M8 | 4 | 0.08-0,25mm² | 0.01Kg |
| **EST-M8-4P-0,25-0,5mm²** | 1-97-00-33-00-EST | M8 | 4 | 0,25-0,5mm² | |
| **EST-M12-4P-0,25-0,75mm²** | 1-97-00-66-00-EST | M12 | 4 | 0,25-0,75mm² | 0.02Kg |

**Legend:** B = xx -pole C = Connection cross-section min.-max.

PLUG / CABLE

## EST-4D Plug Connection 4 pin female






**ADVANTAGES**
- V1 - You determine the cable length of the KAD cable socket yourself
- V2 - optimal laying of the cable
- V3 - simple assembly
- V4 - the wires do not need to be soldered
- Table:

**REMARK**
- M8 - 4 pole socket

**INFO**
- Links:
- Application examples for connection components


| DESIGNATION | ITEM NO. | A | B | C | WEIGHT |
|---|---|---|---|---|---|
| **EST-M8-4D-0.08-0,25mm²** | 1-97-00-36-00-EST | M8 | 4 | 0.08-0,25mm² | 0.01Kg |
| **EST-M8-4D-0,25-0,5mm²** | 1-97-00-37-00-EST | M8 | 4 | 0,25-0,5mm² | |


**Legend:** B = xx -pole C = Connection cross-section min.-max.

PLUG / CABLE

## EST-4P-W Plug Connection 4 pin male - angle






**ADVANTAGES**
- V1 - You determine the cable length of the KAD cable socket yourself
- V2 - optimal laying of the cable
- V3 - simple assembly
- V4 - the wires do not need to be soldered

**REMARK**
- M12 - 4-pin pin

**INFO**
- Links:
- Application examples for connection components

| DESIGNATION | ITEM NO. | A | B | C |
|---|---|---|---|---|
| **EST-M12-4P-0,25-0,75mm²-W** | 1-97-05-10-00-EST | M12 | 4 | 0,25-0,75mm² |

**Legend:** B = xx -pole C = Connection cross-section min.-max.