

PLUG / CABLE

EST-5P Plug Connection 5 pin male







ADVANTAGES

- V1 - You determine the cable length of the KAD cable socket yourself
- V2 - optimal routing of the cable
- V3 - simple assembly
- V4 - the wires do not need to be soldered

REMARK

- M12 - 5-pin pin

INFO

- Links:
- Application examples for connection components


DESIGNATION	ITEM NO.	A	B	C	WEIGHT
EST-M12-5P- 0.25-0.75mm²	1-97-05-04-00-EST	M12	5	0,25-0,75mm²	0.023Kg


Legend: B = xx -pole C = Connection cross-section min.-max.

PLUG / CABLE

EST-5P-W Plug Connection 5 pin male - angle







REMARK

- M12- 5 pole pin

INFO

- Links:
- Application examples for connection components


DESIGNATION	ITEM NO.	A	B	C
EST-M12-5P-0,25-0,75mm²-W	1-97-05-12-00-EST	M12	5	0,25-0,75mm²

Legend: B = xx -pole C = Connection cross-section min.-max.

PLUG / CABLE

KAS-D-SUB Cable plug D-SUB





ADVANTAGES

- V1 - For the gripper connection to the handling portal, e.g. for Engel systems.

REMARK

- - D-SUB male connector 25pin 2-row
- - with 3m cable for dynamic movement, open end
- - Cable Lapp Unitronic FD-P plus 25×0.25 outer diameter 10.4mm
- - Temperature -5°C to 80°C
- - Connector fully assigned according to DIN47100

DESIGNATION	ITEM NO.	A	B	C	WEIGHT
KAS-D-SUB-25-3	1-97-00-80-00-KAS	D-SUB	25-polig	3m	0.472Kg

Legend: A = Cable connector type B = number of cores C = Cable length in metres