
DESIGNATION	ITEM NO.	A	B	C	D	WEIGHT
SVE-M8-4P-3P-3P-37,5	1-97-80-80-00-SVE	M8×1	4-p	3-p	37,5	0.02Kg
SVE-M8-4P-3P-3P-200	1-97-80-81-00-SVE	M8×1	4-p	3-p	200	0.03Kg

DISTRIBUTOR

DVE DUO Terminal





ADVANTAGES

- V1 - less cabling effort (one line saved)

REMARK

- - For collecting two signals in one 4-pin slot
- - Available in M8 and M12 (2×3-pin socket & 1×4-pin pins)


DESIGNATION	ITEM NO.	A	B	WEIGHT
DVE-M8-4P-3P-3P	1-97-80-60-00-DVE	M8	M8	0.014Kg
DVE-M12-4P-3P-3P	1-97-80-64-00-DVE	M12	M8	0.014Kg

Legend: A = 4-pin plug B = 3-pin socket (2x)

DISTRIBUTOR

UVE AND Terminal





ADVANTAGES

- V1 - Saving logic distributor

REMARK

- - Series connection of the sensors


DESIGNATION	ITEM NO.	A	B	WEIGHT
UVE-M8-3P-3P-3P	1-97-80-50-00-UVE	M8	M8	0.014Kg

Legend: A = 3-pin connector B = 3-pin socket (2x)

DISTRIBUTOR

EVE Electric Terminal





INFO

- Description:
- - 5-metre PUR cable, open end
- - available for M8 3-pin or M8 4-pin
- - Suitable for use with drag chains
- - Number of bending cycles: 5 million
- Links:
- EST-3P – 3-pin electrical plug<\/a>
- EST-4P – 4-pole electrical plug
- Application examples for connection components

DOCUMENTS

- Datenblatt_EVE-M8-4-3P.pdf
- Path
- Datenblatt_EVE-M8-4P.pdf
- Path
- Datenblatt_EVE-M8-8-3P.pdf
- Path

DESIGNATION	ITEM NO.	A	B	WEIGHT
EVE-M8-4-3P	1-97-80-10-00-EVE	4	3	0.354Kg